


PHYSICAL SPECIFICATION



Nominal Voltage		12V
Nominal Capacity (20HR)		1.2Ah
Dimension	Length	97±1mm (3.82 inches)
	Width	44±1mm (1.73 inches)
	Container Height	53±1mm (2.09 inches)
	Total Height	58±1mm (2.28 inches)
Weight		Approx. 0.55 Kg ±3% (1.21lbs)
Standard Terminal		F1-Fasten Tab No.187E(F1)



Shimastu NP series AGM VRLA Batteries have been developed as general purpose batteries, they're valve-regulated lead acid batteries with high quality Absorbed Glass Mat (AGM) separators & high purity raw materials, featured by perfectly good performance and reliable standby service life.


Features:

1. Non-spillable
2. Sealed and Maintenance-free Operation
3. High Quality and High Reliability
4. Less gassing, low Self-discharge
5. Low internal resistance
6. Long design life up to 6 years in float service at 25°C (77 °F)

ELECTRICAL SPECIFICATION

Characteristics			
Capacity	20 hour rate	(0.06A)	1.2Ah
	10 hour rate	(0.112A)	1.12Ah
	5 hour rate	(0.204A)	1.02Ah
	3 hour rate	(0.3A)	0.9Ah
	1 hour rate	(0.66A)	0.66Ah
Capacity affected by temperature	40°C (104 °F)		102%
	25°C (77 °F)		100%
	0°C (32 °F)		85%
Max Discharge Current	12A(5 Sec)		
Short Circuit Current	64A		
Internal Resistance	Full charged battery (25°C, 77 °F) 50mΩ		
Constant Voltage Charge	Cycle	Initial Charging Current less than 0.36A Voltage 14.4~15.0V at 25°C (77 °F) Temperature Coefficient -30mV/°C	
	Standby	No limit on Initial Charging Current Voltage 13.5~13.8V at 25°C (77 °F) Temperature Coefficient -20mV/°C	

Discharge curves @ 25°C (77 °F)




CONSTANT CURRENT DISCHARGE RATING A@25°C

F.V/TIME	5MIN	10MIN	15MIN	30MIN	1HR	3HR	5HR	10HR	20HR
1.60V	4.354	2.709	2.040	1.246	0.733	0.337	0.224	0.118	0.063
1.65V	4.080	2.571	1.971	1.191	0.708	0.327	0.219	0.117	0.062
1.70V	3.737	2.469	1.920	1.083	0.685	0.318	0.213	0.115	0.061
1.75V	3.669	2.400	1.851	1.029	0.660	0.309	0.208	0.113	0.060
1.80V	3.291	2.297	1.687	0.953	0.636	0.300	0.204	0.112	0.059


CONSTANT POWER DISCHARGE RATING WATT PER CELL@25°C

F.V/TIME	5MIN	10MIN	15MIN	30MIN	1HR	3HR	5HR	10HR	20HR
1.60V	7.218	4.602	3.566	2.264	1.378	0.642	0.432	0.232	0.123
1.65V	6.841	4.455	3.497	2.187	1.338	0.627	0.423	0.229	0.121
1.70V	6.409	4.356	3.458	2.008	1.302	0.612	0.413	0.226	0.120
1.75V	6.431	4.311	3.382	1.926	1.262	0.598	0.405	0.223	0.118
1.80V	5.892	4.200	3.125	1.803	1.223	0.582	0.398	0.220	0.117

Cycle service life




Trickle(or float) service life



Storage time(months)



Temperature and discharge capacity



Charging characteristic



Storage Temperature	Supplementary Charge Interval	Charge Method
≤20°C	Every 12 months	Less or 24 hours with a constant voltage of 2.3V/cell
20-30°C	Every 8 months	12-18 hours with a constant voltage of 2.45V/cell
≥30°C	Storage to be avoided	8-12 hours with a constant current of 0.05CA

APPLICATIONS

Standby Usage:

- UPS
- Emergency Lights
- Alarm Systems
- Telecommunication Systems

Cyclic Usage:

- Medical Equipments
- Electric Instruments
- Toys
- Camcorder and Solar Systems

Motive Usage:

- Golf Cars
- Wheelchairs
- Lawnmowers
- Motorcycle

(Note) All above information shall be changed without prior notice, Shimastu reserves the right to explain and update the latest information.